

A ~~GR 98 P 1418 P~~~~Description~~~~Method and radio communications system for connection control during calls from/to radio subscribers~~

5

The invention relates to a method for connection control during calls from/to radio subscribers in a radio communications system, and to a corresponding radio communications system.

A 10

Radio communications systems are used to supplement or expand existing public or private communications systems. For example, in contrast to public communications systems such as the public telephone network, radio communications systems can at least partially use wire-free communications connections. As is known, such radio communications systems have radio devices which can be combined to form at least one radio subsystem, for linking, without any wires, communications terminals which each allow access by radio subscribers, and switching devices for switching through connections, signaling connections, and traffic channel connections. A radio subsystem can normally be assigned an associated radio area for supervising the radio subscribers moving with their communications terminals in that area. This means that switching centers, radio devices and communications terminals which are networked to one another in a radio communications system can be connected to one another in a very large number of ways.

30

Each connection on the basis of an outgoing or incoming call, in which at least one radio subscriber is involved, must normally be routed via the switching center. For certain areas, particularly remote areas - for example islands, mountain valleys, deserts, etc. -

35

which are controlled by a radio subsystem with appropriate radio devices, it may not be economically worthwhile to use

002260 21894960

A ~~GR 98 P 1418~~  
A ~~PCT/DE99/00734~~

- 2 -

and operate a dedicated switching center for each area. The use of the existing telecommunications resources should be optimized for this situation. Furthermore, a significant number of countries have no infrastructure to produce the link between the radio devices and one or more central switching centers in a radio communications system in order to use telecommunications services at a reasonable cost.

WO 95/24789 discloses a method for connection control in a radio communications system, which has transcoder units, at a distance from the base stations, for coding and decoding voice signals. In the case of a call between radio subscribers within a radio area or in the case of a call between radio subscribers in different radio areas, only signaling connections are switched through to the switching center. The traffic channel connections are switched by the radio subsystem itself for the first-mentioned case, and are switched between different radio subsystems for the second-mentioned case.

US 5,081,703 discloses a satellite communications system for rural areas, in which signals received from the satellites are converted by conversion units into signals for a switching center, and vice versa. In this case, the conversion units communicate with mobile stations which are located in predetermined geographical areas.

*Summary of the Invention*  
One object of the present invention is thus to specify a method and a radio communications system which improves the connection control during calls from/to radio subscribers.

According to the invention, this object is achieved by the features of patent claim 1 with regard to the method, and by the features of patent claim 10 with regard to the radio communications system. Developments of the invention can be found in the dependent claims.

Based on a radio communications system having at least one radio subsystem for access by the radio

subscribers in an associated radio area and having at least one switching center for switching through connections, the method and the radio communications system according to the invention provide for the  
5 connections between the radio subsystem and the switching center to be routed via a radio transmission unit in such a way,

- that, in the case of a call within a radio area between radio subscribers within the same radio  
10 area, or in the case of a call between radio subscribers in different radio areas, only signaling connections are switched through from the radio transmission unit to the switching center, and

- that traffic channel connections are switched  
15 by the radio transmission unit between a first radio

002260 " 27894960



5 Since only the signaling connections are  
switched via the radio transmission unit - preferably  
in the form of a satellite - to the switching center,  
while the traffic channel connections are switched  
either locally in the radio subsystem or in the radio  
10 transmission unit, the connection control can be  
optimized with a dynamic switching capacity -  
particularly for a remote radio area without its own  
switching center. It is thus sufficient to equip each  
such radio area only with radio devices rather than  
15 with an oversize switching center, and to provide the  
through-switching functions of a switching center for  
traffic channel connections which are to be used as  
optimally as possible, in the radio subsystem or in the  
radio transmission unit according to the invention. A  
20 further advantage of the subject matter of the  
invention over a solution in which the traffic channel  
connections are always switched through as far as the  
switching center is that, in the case of a call within  
a radio area, no traffic channel connections whatsoever  
25 need be switched in the radio transmission unit, and in  
the case of a call between radio subscribers in  
different radio areas, fewer traffic channel  
connections need be switched in the radio transmission  
unit - since the switching center is bypassed for both  
30 parts of the call connection. In both cases, this  
result in an increase in capacity with regard to the  
transmission bandwidth in the radio transmission unit,  
which is at its greatest when the traffic channel  
connections with the user information are switched  
35 through in the case of a call within a radio area.

According to one advantageous development of the invention, even in the case of a call which relates to a radio subscriber and a subscriber of another communications system,

only the signaling connections are switched through from the radio transmission unit to the switching center, while the traffic channel connections between the radio communications system and the other communications system are switched by the radio transmission unit. This additionally results in an increase in capacity in the case of a call in which traffic channel connections from the other communications system, for example, a cable-based public communications network (PLMN), would normally have to be switched to the switching center of the radio communications system but, according to the development, are actually passed on directly from the radio transmission unit to the radio subsystem.

According to another development of the invention, it has been found to be advantageous for control information to be sent back from the switching center via a switched-through signaling connection, on the basis of which control information the radio subsystem and/or the radio transmission unit cause/causes the traffic channel connections. It is thus possible in a simple way for the radio subsystem or the radio transmission unit to use the received control information to decide whether it should or should not switch through the user connections locally.

In this case, it is particularly advantageous if an identifier to identify trunks which are in each case used for the call in the switching center are also sent back from the switching center via a switched-through signaling connection, <sup>and</sup> on the basis of <sup>the</sup> ~~which~~ identifier, the radio subsystem checks for the presence of a call within a radio area, and causes the switching of the traffic channel connections. The switching center uses this information to inform the radio subsystem in a simple way that the traffic channel connections can be switched through locally, since this is a call within the radio area.

Other developments of the invention provide for the switching of the signaling connections and of the traffic channel connections in the respective radio subsystem to be controlled by interworking units with a through-switching capability, and for the switching of the signaling connections to the switching center to be controlled by further interworking units with a through-switching capability.

It has also been found to be advantageous for the switching of the signaling connections and of the traffic channel connections for the uplink transmission direction from the communications terminal to the radio subsystem to be carried out after carrying out a transcoder and data rate adaptation function, and for ~~that for~~ the downlink transmission direction from the radio subsystem to the communications terminal to be carried out before carrying out the transcoder and data rate adaptation function in the respective radio subsystem.

*BRIEF DESCRIPTION OF THE DRAWINGS*  
The subject matter of the invention will be explained in more detail in the following text with reference to drawing illustrations, in which:

Figure 1 ~~shows the~~ <sup>is a</sup> block diagram of a radio communications system,

Figure 2 ~~shows~~ <sup>is</sup> a schematic illustration of the connection control process according to the invention for a call within a radio area, and

Figure 3 ~~shows~~ <sup>is</sup> a schematic illustration of the connection control process according to the invention for a call between radio subscribers in different radio areas.

*DESCRIPTION OF THE PREFERRED EMBODIMENT*  
Figure 1 shows the block diagram of a radio communications system KN, which normally has a number of radio subsystems to control the radio resources in radio areas in which there are radio subscribers. The chosen example shows

two radio subsystems RSS, RSS\* for radio coverage of the associated radio areas RRA, RRA\* (Remote Radio Area), via which communications terminals - mobile stations MS - which allow access to the radio subscribers, can be connected via a radio interface. Devices in a radio communications system which is operated in accordance with the GSM method have been chosen as examples of the radio devices. However, the invention is not limited to GSM systems and can be used irrespective of the access technology for radio transmission, for example, TDMA (Time Division Multiple Access), FDMA (Frequency Division Multiple Access), CDMA (Code Division Multiple Access) <sup>the invention may be used</sup> ~~and~~ in other radio communications systems as well. Furthermore, the radio communications system KN has at least one switching center MSC for switching through connections, that is to say, signaling connections and user channel connections, for calls from/to the radio subscribers. A gateway from the radio communications system KN to another communications system - in the present example to the public telephone network PLMN - is feasible, so that the connections for calls between a subscriber in the other communications system and a radio subscriber in the radio communications system KN can also be controlled according to the subject matter of the invention.

As is known, every radio subsystem RSS, RSS\* has a base station BS, BS\*, as the device of the opposite end to the mobile stations MS, for communication via the radio interface. A base station controller BSC, BSC\* is connected to the base station BS, BS\* in order to manage the radio resources - such as radio channel assignment. A transcoder and data rate adaptation unit TRAU, TRAU\* is connected to the base station controller BSC, BSC\* and is used to match the transmission rate - for example 16 kbit/s - used in the radio subsystem RSS, RSS\* and on the radio interface, and the transmission rate - for example, 64 kbit/s - processed in the switching center MSC to one another in

~~A CR 98 P 1418~~

- 6a -

both transmission directions (uplink and downlink).

000000 27894960



Furthermore, the transcoder and data rate adaptation unit TRAU, TRAU\* carries out the task of decompressing the information which was transmitted in compressed form via the radio interface.

5 In order to produce a link between the radio  
subsystems RSS, RSS\* without a dedicated switching  
A center - in particular, for remote radio areas - and the  
switching center MSC wherever it is located, a radio  
transmission unit UE is connected in between. For  
10 connection control, this means that, for calls within a  
radio area (Intra Remote Radio Area call) - see case  
(1) - which take place between radio subscribers within  
the same radio area RRA, the user connections ni are  
switched through locally by the associated radio  
15 subsystem RSS. Only the signaling connections si are  
passed on via the radio transmission unit UE to the  
switching center MSC. The transmission bandwidth of the  
radio transmission unit UE, which is preferably in the  
form of a satellite, is utilized more economically by  
20 local through-switching for the user connections ni -  
which contain the user information in the form of voice  
and data - since, otherwise, the first partial user  
connection of the calling radio subscriber and the  
second partial user connection of the called radio  
25 subscriber would have to be passed via the satellite  
for every call. The local through-switching functions  
in the radio subsystem RSS are provided in an  
interworking unit IWU, which is preferably connected to  
the transcoder and data rate adaptation unit TRAU, or  
30 is integrated in it.

A During the connection <sup>set</sup>~~setting~~-up process, the  
switching center MSC normally assigns transmission  
channels to the radio subsystem RSS for both radio  
subscribers. In doing so, it confirms - using known GSM  
35 procedures to determine the locations - that both radio  
subscribers are located in the same radio area RRA. The  
switching center MSC thus sends an identifier for  
identification of the respective

002260 21894960

trunks used for the two connection elements in the switching center MSC, via a signaling connection si to the radio area RRA, on the basis of which the interworking unit IWU of the radio subsystem RSS identifies the presence of the call within a radio area, and initiates internal switching of the traffic channel connections. The signaling connections si are always switched by the radio subsystem RSS via the satellite UE to the switching center MSC. The satellite UE uses the information about the presence of the call within a radio area to identify that it need not provide any transmission channels for the user connections ni.

In the case of a call between radio subscribers who are located in different radio areas RRA, RRA\* see case (2), connection control is carried out in such a way that the satellite UE once again switches through only the signaling connections si to the switching center MSC, and switches the traffic channel connections ni between the radio subsystem RSS and the radio subsystem RSS\*. The through-switching process for the traffic channel connections ni in the satellite UE is assisted by the interworking unit IWU, IWU\* assigned to the respective radio subsystem RSS, RSS\*. This means that the satellite UE can directly link transmission channels for voice signal transmission which are associated with different radio subsystems RSS, RSS\* or radio areas RRA, RRA\* without having to include the switching center MSC *i.e., bypassing the switching center* (bypassing). This leads to an improvement in capacity with regard to the transmission bandwidth of the satellite UE. The signaling connections si for such calls are also always switched from the respective radio subsystem RSS, RSS\* via the satellite UE to the switching center MSC.

A further example relating to the saving of bandwidth in the satellite UE is to bypass the switching center MSC for connection control for traffic channel connections ni which need to be switched when calls occur between the radio subscriber

and the subscriber in the other communications system PSTN. Only the signaling connections si from the satellite UE to the switching center MSC are switched through in the same way as that described above while, in contrast, the traffic channel connections ni from the satellite UE are switched through directly between the radio subsystem - for example, the radio subsystem RSS - of the radio communication system KN responsible for the radio subscriber, and the communications system PSTN responsible for the other subscriber. The communications system PSTN also has an interworking unit IWU with a through-switching capability to support direct switching of the traffic channel connections ni - see case (3) in Figure 1.

Figure 2 shows a schematic illustration of the connection control process according to the invention with the devices involved in this process for a call within a radio area, as shown in case (1) in Figure 1. In this case, the routing of the traffic channel connections ni is shown as a dashed-dotted line, and the routing of the signaling connections si is shown as a dotted line. The call in the radio area RRA is initiated from the mobile station MS of a first radio subscriber, and its destination is a second radio subscriber. The radio subsystem RSS handles the call in accordance with the known GSM procedures. The switching center MSC, which is coupled via the satellite UE to the radio subsystem RSS, likewise uses the known GSM procedures to identify the fact that the called radio subscriber is located in the same radio area RRA. It thus generates the control information intra, ~~using~~<sup>via</sup> which the presence of the call within the radio area can be checked. Furthermore, the switching center MSC produces an identity code cic (circuit identity code) which identity code the trunks used in the switching center MSC for the radio subscribers involved with the call. Both signaling information items cic, intra are sent from an interworking unit IWU2, which is arranged in the interworking unit IWU in the switching center

002250 21394960

~~A CR 98 P 1418~~

- 9a -

MSC, via the satellite UE to an

002260 27894960

interworking unit IWU1 in the interworking unit IWU of the relevant radio subsystem RSS on a signaling connection si.

The interworking unit IWU or the interworking unit IWU1 in the radio subsystem RSS evaluates the received information cic, intra to identify the fact that local through-switching of the traffic channel connections ni is possible, and initiates the through-switching function triggered via the received signaling information. The traffic channel connections ni are thus routed via the interworking unit IWU1 of the interworking unit IWU directly to the radio devices in the radio subsystem - TRAU, BSC and BS - back and from there to the mobile station MS of the called radio subscriber *(see the bold arrows)* ~~see the arrows printed in bold.~~

Figure 3 shows a schematic illustration of the connection control process according to the invention with the devices involved in this process for a call between radio subscribers in different radio areas RRA, RRA\* as shown in case (2) in Figure 1. In this case, the routing of the traffic channel connections ni - analogously to the illustration in Figure 2 - is shown as a dashed-dotted line, and the routing of the signaling connections si is shown as a dotted line. The call in the radio area RRA is initiated from the mobile station MS of a first radio subscriber, and its destination is a second radio subscriber. The radio subsystem RSS handles the call in accordance with the known GSM procedures. The switching center MSC, which is coupled to the radio subsystem RSS via the satellite UE, likewise uses the known GSM procedures to identify the fact that the called radio subscriber is located in another radio area RRA\*. It thus generates a control information item inter which indicates that the call is taking place between radio subscribers in different radio areas RRA, RRA\*. It also receives the identity code cic (circuit identity code) for the trunks used in the switching center MSC. The signaling information is sent from the interworking unit IWU2

002250 27894960

via the satellite UE on a signaling connection si and thus  
 A ~~to~~ ~~lacuna~~ the switching of the traffic channel connections ni  
 in the interworking unit IWU1 - bypassing the switching  
 center MSC - to the radio subsystem RSS\*. In this subsystem,  
 5 the interworking unit IWU\* has an interworking unit IWU3  
 which is intended to switch the traffic channel connections  
 ni through for the call. The routing of the traffic channel  
 connections ni from the interworking unit IWU1 to the  
 10 satellite UE is thus followed by direct connection of the  
 satellite UE to the interworking unit IWU3. The connection  
 is controlled by the interworking unit IWU2. In the radio  
 subsystem RSS\*, the interworking unit IWU3 switches the  
 traffic channel connections ni through, so that the user  
 information - primarily voice signals - is passed to the  
 15 radio devices - TRAU\*, BSC\* and BS\* - and from there to the  
 mobile station MS of the called radio subscriber ~~see the~~  
 A ~~(see the bold arrows)~~  
~~arrows printed in bold.~~

In addition to the interworking unit IWU2, the  
 switching center MSC has a further interworking unit IWU4,  
 20 from which signaling information - such as the control  
 information inter - relating to the radio subscriber located  
 in the radio area RRA\* and to the trunks used for the second  
 connection element, can be sent back via the satellite UE.  
 The through-switching process for connection control  
 25 according to the invention, which switches the traffic  
 channel connections locally in the radio subsystem or  
 directly in the satellite, requires only half the normal  
 bandwidth when each connection element is passed via the  
 switching center MSC.

30 A procedure analogous to that in Figure 2 can also  
 be used in case (3) shown in Figure 1, by the through-  
 switching functions acting directly via the satellite UE on  
 the traffic channel connections between the communications  
 system PSTN and the radio subsystem RSS of the radio  
 35 communications system KN. This depends on the switching  
 center MSC being linked to the communications system PSTN  
 via a radio transmission device UE, preferably a satellite.  
 In this

002260 21894960

case as well, the bypassing of the switching center MSC for voice signal transmission leads to an improvement in capacity, since none of the connection elements needs to be switched to the switching center MSC.

5       The subject matter of the invention means, in particular, that remote radio areas need be equipped only with those radio devices which are then connected only for signaling purposes via a radio transmission device UE to any desired switching center MSC in the radio communications system, and they themselves  
0       locally switch the traffic information through, on a traffic-channel basis, or switch it directly via the radio transmission device.

$$A_3$$

Figure 1 consists of 12 histograms arranged in a 6x2 grid. Each histogram represents the frequency distribution of the number of non-zero elements in the vector  $x$  for a specific value of  $n$ . The x-axis for all histograms is 'Number of non-zero elements in  $x$ ' with major ticks at 0, 20, 40, 60, 80, 100, and 120. The y-axis is 'Frequency' with major ticks at 0, 20, 40, 60, 80, and 100. The histograms are labeled with  $n$  values: 10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, and 120. As  $n$  increases, the distribution becomes more concentrated at 0 non-zero elements, and the frequency at 0 increases significantly.